


SOLO 16 PLUS STUCCHI

13° ULTRA NARROW BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The ultra narrow beam in our 12.60W 1200lm module has a peak intensity of 16929cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

CATEGORY IP20

MATERIAL Machined AL 6063-T6 | Machined Brass

PAN 360°

TILT 90°

LOCKABLE Pan

WEIGHT 395g 570g* | 0.87lb 1.25lb*

WATTAGE 12.60W

FORWARD VOLTAGE 48V

SUPPLY TYPE Constant Voltage

DRIVER LOCATION Remote AC to 48VDC

DIMMING DALI | 0-10V | 1-10V | Casambi

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES

FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

NOMINAL LUMENS 1200lm

DELIVERED LUMENS 1127lm

COLOUR TEMPERATURE 2400K | 2700K | 3000K

ACCESSORY HOLDER Separate

ACCESSORIES Lenses | Louver 55mm (2.16")

TM65 17.52kgCO₂e

TM66 2.4

BEAM ANGLE 13°

CRI 92 TYP - 2400K | 98 TYP - 2700K/3000K

TM-30 RF: 95 RG: 101


WARRANTY 5 Years

LIFETIME L90B10 50,000hrs

STANDARDS



Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052C	<div>T White 9016</div> <div>B Black 9005</div>	<div>T White 9016</div> <div>B Black 9005</div> <div>A Brushed Aluminium</div> <div>R Rubbed Bronze*</div> <div>P Polished Brass*</div> <div>S Brushed Brass*</div>	<div>2490 2400K 90CRI</div> <div>2798 2700K 98CRI</div> <div>3098 3000K 98CRI</div> <div>4095 4000K 95CRI</div>	<div>13 Ultra Narrow 13°</div> <div>15 Narrow 15°</div> <div>25 Medium 25°</div> <div>40 Flood 40°</div> <div>50 Wide Flood 50°</div>	<div>A 0-10V</div> <div>C Casambi</div> <div>D DALI</div>

Example Code: 1052C - TT - 279815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

15° NARROW BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The narrow beam in our 12.60W 1200lm module has a peak intensity of 14173cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

CATEGORY IP20

MATERIAL Machined AL 6063-T6 | Machined Brass

PAN 360°

TILT 90°

LOCKABLE Pan

WEIGHT 395g 570g* | 0.87lb 1.25lb*

WATTAGE 12.60W

FORWARD VOLTAGE 48V

SUPPLY TYPE Constant Voltage

DRIVER LOCATION Remote AC to 48VDC

DIMMING DALI | 0-10V | 1-10V | Casambi

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES

FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

NOMINAL LUMENS 1200lm

DELIVERED LUMENS 1104lm

COLOUR TEMPERATURE 2400K | 2700K | 3000K

ACCESSORY HOLDER Separate

ACCESSORIES Lenses | Louver 55mm (2.16")

TM65 17.52kgCO₂e

TM66 2.4

BEAM ANGLE 15°

CRI 92 TYP - 2400K | 98 TYP - 2700K/3000K

TM-30 RF: 95 RG: 101


WARRANTY 5 Years

LIFETIME L90B10 50,000hrs

STANDARDS



Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052C	<div>T White 9016</div> <div>B Black 9005</div>	<div>T White 9016</div> <div>B Black 9005</div> <div>A Brushed Aluminium</div> <div>R Rubbed Bronze*</div> <div>P Polished Brass*</div> <div>S Brushed Brass*</div>	<div>2490 2400K 90CRI</div> <div>2798 2700K 98CRI</div> <div>3098 3000K 98CRI</div> <div>4095 4000K 95CRI</div>	<div>13 Ultra Narrow 13°</div> <div>15 Narrow 15°</div> <div>25 Medium 25°</div> <div>40 Flood 40°</div> <div>50 Wide Flood 50°</div>	<div>A 0-10V</div> <div>C Casambi</div> <div>D DALI</div>

Example Code: 1052C - TT - 279815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

25° MEDIUM BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The medium beam in our 12.60W 1200lm module has a peak intensity of 5149cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

CATEGORY IP20

MATERIAL Machined AL 6063-T6 | Machined Brass

PAN 360°

TILT 90°

LOCKABLE Pan

WEIGHT 395g 570g* | 0.87lb 1.25lb*

WATTAGE 12.60W

FORWARD VOLTAGE 48V

SUPPLY TYPE Constant Voltage

DRIVER LOCATION Remote AC to 48VDC

DIMMING DALI | 0-10V | 1-10V | Casambi

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES

FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

NOMINAL LUMENS 1200lm

DELIVERED LUMENS 1072lm

COLOUR TEMPERATURE 2400K | 2700K | 3000K

ACCESSORY HOLDER Separate

ACCESSORIES Lenses | Louver 55mm (2.16")

TM65 17.52kgCO2e

TM66 2.4

BEAM ANGLE 25°

CRI 92 TYP - 2400K | 98 TYP - 2700K/3000K

TM-30 RF: 95 RG: 101


WARRANTY 5 Years

LIFETIME L90B10 50,000hrs

STANDARDS



Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052C	<div>T White 9016</div> <div>B Black 9005</div>	<div>T White 9016</div> <div>B Black 9005</div> <div>A Brushed Aluminium</div> <div>R Rubbed Bronze*</div> <div>P Polished Brass*</div> <div>S Brushed Brass*</div>	<div>2490 2400K 90CRI</div> <div>2798 2700K 98CRI</div> <div>3098 3000K 98CRI</div> <div>4095 4000K 95CRI</div>	<div>13 Ultra Narrow 13°</div> <div>15 Narrow 15°</div> <div>25 Medium 25°</div> <div>40 Flood 40°</div> <div>50 Wide Flood 50°</div>	<div>A 0-10V</div> <div>C Casambi</div> <div>D DALI</div>

Example Code: 1052C - TT - 279815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

40° FLOOD BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The flood beam in our 12.60W 1200lm module has a peak intensity of 2358cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

CATEGORY IP20

MATERIAL Machined AL 6063-T6 | Machined Brass

PAN 360°

TILT 90°

LOCKABLE Pan

WEIGHT 395g 570g* | 0.87lb 1.25lb*

WATTAGE 12.60W

FORWARD VOLTAGE 48V

SUPPLY TYPE Constant Voltage

DRIVER LOCATION Remote AC to 48VDC

DIMMING DALI | 0-10V | 1-10V | Casambi

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES

FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

NOMINAL LUMENS 1200lm

DELIVERED LUMENS 987lm

COLOUR TEMPERATURE 2400K | 2700K | 3000K

ACCESSORY HOLDER Separate

ACCESSORIES Lenses | Louver 55mm (2.16")

TM65 17.52kgCO₂e

TM66 2.4

BEAM ANGLE 40°

CRI 92 TYP - 2400K | 98 TYP - 2700K/3000K

TM-30 RF: 95 RG: 101


WARRANTY 5 Years

LIFETIME L90B10 50,000hrs

STANDARDS



Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052C	<div>T White 9016</div> <div>B Black 9005</div>	<div>T White 9016</div> <div>B Black 9005</div> <div>A Brushed Aluminium</div> <div>R Rubbed Bronze*</div> <div>P Polished Brass*</div> <div>S Brushed Brass*</div>	<div>2490 2400K 90CRI</div> <div>2798 2700K 98CRI</div> <div>3098 3000K 98CRI</div> <div>4095 4000K 95CRI</div>	<div>13 Ultra Narrow 13°</div> <div>15 Narrow 15°</div> <div>25 Medium 25°</div> <div>40 Flood 40°</div> <div>50 Wide Flood 50°</div>	<div>A 0-10V</div> <div>C Casambi</div> <div>D DALI</div>

Example Code: 1052C - TT - 279815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

50° WIDE FLOOD BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The wide flood beam in our 12.60W 1200lm module has a peak intensity of 1545cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

CATEGORY IP20

MATERIAL Machined AL 6063-T6 | Machined Brass

PAN 360°

TILT 90°

LOCKABLE Pan

WEIGHT 395g 570g* | 0.87lb 1.25lb*

WATTAGE 12.60W

FORWARD VOLTAGE 48V

SUPPLY TYPE Constant Voltage

DRIVER LOCATION Remote AC to 48VDC

DIMMING DALI | 0-10V | 1-10V | Casambi

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES

FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

NOMINAL LUMENS 1200lm

DELIVERED LUMENS 979lm

COLOUR TEMPERATURE 2400K | 2700K | 3000K

ACCESSORY HOLDER Separate

ACCESSORIES Lenses | Louver 55mm (2.16")

TM65 17.52kgCO2e

TM66 2.4

BEAM ANGLE 50°

CRI 92 TYP - 2400K | 98 TYP - 2700K/3000K

TM-30 RF: 95 RG: 101


WARRANTY 5 Years

LIFETIME L90B10 50,000hrs

STANDARDS



Photometry shown is for 3000K module. Please enquire for other CCT photometry.



MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052C	<div>T White 9016</div> <div>B Black 9005</div>	<div>T White 9016</div> <div>B Black 9005</div> <div>A Brushed Aluminium</div> <div>R Rubbed Bronze*</div> <div>P Polished Brass*</div> <div>S Brushed Brass*</div>	<div>2490 2400K 90CRI</div> <div>2798 2700K 98CRI</div> <div>3098 3000K 98CRI</div> <div>4095 4000K 95CRI</div>	<div>13 Ultra Narrow 13°</div> <div>15 Narrow 15°</div> <div>25 Medium 25°</div> <div>40 Flood 40°</div> <div>50 Wide Flood 50°</div>	<div>A 0-10V</div> <div>C Casambi</div> <div>D DALI</div>

Example Code: 1052C - TT - 279815 - D


*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

DRIVER COMPATIBILITY

60W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 3
MIN DIM LEVEL N/A Dimming direct to track
VOLTAGE REGION 230V
FOR NORTH AMERICA No
WATTAGE 60W
OUTPUT VOLTAGE 48V
SUPPLY TYPE Constant Voltage
DRIVER LOCATION Remote



ORDER CODE PSCV-60-48-N1-MW

LENGTH 162mm (6.38")


WIDTH 42mm (1.65")

HEIGHT 32mm (1.23")



100W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 6
MIN DIM LEVEL N/A Dimming direct to track
VOLTAGE REGION 230V
FOR NORTH AMERICA No
WATTAGE 100W
OUTPUT VOLTAGE 48V
SUPPLY TYPE Constant Voltage
DRIVER LOCATION Remote



ORDER CODE PSCV-100-48-N1-MW

LENGTH 190mm (7.48")


WIDTH 52mm (2.04")

HEIGHT 37mm (1.46")



96W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 6
MIN DIM LEVEL N/A Dimming direct to track
VOLTAGE REGION 120V & 277V
FOR NORTH AMERICA Yes
WATTAGE 96W
OUTPUT VOLTAGE 48V
SUPPLY TYPE Constant Voltage
DRIVER LOCATION Remote



ORDER CODE USCV-96-48-N1-SC-EN

LENGTH 220mm (8.66")

WIDTH 95mm (3.74")

HEIGHT 40mm (1.57")




SOLO 16 SERIES SPOTLIGHT ACCESSORIES

FOR USE WITH SOLO 16 INTENSE | PLUS | DYNAMIC WHITE

ACCESSORIES

The Solo 16 series track and surface spotlights can accommodate accessories with a snap in accessory holder.



Double Accessory Holder

Can hold 2 accessories

HEIGHT 14mm (0.551")
DAIMETER 63mm (2.480")




PART CODE 254-BK

Honeycomb Louvre

Enhances glare control

THICKNESS 3.2mm (0.126")
DAIMETER 55mm (2.165")



PART CODE 995-55-BK

1/4 CTO Dichroic

CCT warming - approx 300K

THICKNESS 1.8mm (0.071")
DAIMETER 55mm (2.165")




PART CODE 997-1/4CTO-55

Softening Lens

Heavy Diffusion of beam

THICKNESS 3.2mm (0.126")
DAIMETER 55mm (2.165")



PART CODE 991-55

Linear Lens

Elongates beam

THICKNESS 3.9mm (0.154")
DAIMETER 55mm (2.165")



PART CODE 992-55